

Polymer thixotropic transparent paste with high viscosity for glueing and fixing marbles, stones and tiles



## PRODUCT BENEFITS

- Polyester base thixotropic transparent glue
- Fast setting and curing time
- Easily to apply and polish
- Good UV stability
- Colors can be mixed as per desired
- Polishable and grindable after hardening

## APPLICATION AREAS

- Walls
- Floors
- Showers
- Damp areas
- Tile on tile applications
- Dry areas
- Worktops

## USAGE

### RECOMMENDED SURFACES

- Granite,
- Marbles,
- Tiles,
- Sandstones,
- Cementitious tiles

## COVERAGE

100- 250 sq. ft. per kg

## PACKAGING SIZE

1 L

## TECHNICAL DATA

• Form	Thixotropic Gel
• Mixing Ratio	100 (resin) : 2 to 4 (hardener) pbw
• Density	1.25 - 1.50 g/cm <sup>3</sup>
• Shelf Life	6 months (When stored below 35 Deg C)
• Pot Life	15 minutes
• Curing Time (Touch Dry) 25 - 50 Deg C	10-15 Minutes
• Curing Time (Touch Dry) 15 - 25 Deg C	15-20 Minutes
• Curing Time (Touch Dry) 5 - 15 Deg C	20-50 Minutes
• Curing Time (Full Cure)	3- 5 Hours

## INSTRUCTIONS

### SURFACE PREPARATION

- The substrate must be thoroughly cleaned and should free of moisture, dirt, oil and grease etc.

### PREPARING THE MIX

- Ensure proper and thorough mixing of resin (PART A) and hardener (PART B) before applying. DO NOT MIX ANY SOLVENTS.

### APPLICATION METHOD

- Use Gloves during application. Follow manufacturer's instructions of for using gloves.
- Mask any surface not intended to be treated.
- The joints must be sealed with RachTR Back-Seal to avoid any penetration in to the substrate.
- Mix part A and B homogeneously and apply it on the edges of substrate. DO NOT ALLOW EXCESS MATERIAL TO DRY ON SURFACE.
- If excess mastic is not wiped off, residue appears, mechanically remove the cured epoxy.

- A full cure of R105 T is achieved after 2 hours; foot traffic may begin after 1-2 hours.
- Clean tools with appropriate solvent immediately after application and allow them dry in a well ventilated area.
- After 2-3 hours, the treated part can be further processed and transported.
- Hardener portion more than 5% will reduce adhesion and deteriorate surface drying.
- Hardener portion less than 1% will delay the hardening and can affect the desired quality.
- The low temperatures can significantly affect the curing process.

## EMERGENCY/FIRST AID

- Ingestion: Do not induce vomiting. Call a physician
- Eye Contact: Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. Call a physician if eye irritation persists.
- Skin Contact: Wash skin with mild soap and water. Call a physician if skin irritation persists. Wash clothes before wearing again.
- Inhalation: Fresh air. Call a physician if respiratory irritation persists.

## STORAGE AND HANDLING

May be harmful if swallowed. May cause skin, eye and respiratory irritation.

Do not spray. Avoid prolonged exposure to vapors.

Use in a well ventilated area. Do not ingest.

KEEP OUT OF THE REACH OF THE CHILDREN.

Do not freeze or store above 40 °C.

Do not mix with other chemicals.



RachTR Chemicals Pvt. Ltd.  
D-10, 2nd Floor, DDA LSC Naraina Vihar, New Delhi -110028  
Tel. +91-7827191824, +91-11-40392557  
Web: [www.rachtr.com](http://www.rachtr.com) - Email: [marketing@rachtr.com](mailto:marketing@rachtr.com)  
Manufactured in INDIA

*The above information is based on the latest stage of our development and application technology. Due to multiplicity of influencing factors, this information must be considered as non-binding. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.*